



PROBLEM 4.10

4.9 through 4.11 Two vertical forces are applied to a beam of the cross section shown. Determine the maximum tensile and compressive stresses in portion BC of the beam.




SOLUTION



	A	\bar{y}_0	$A\bar{y}_0$
①	18	5	90
②	18	1	18
Σ	36		108

$$\bar{Y}_0 = \frac{108}{36} = 3 \text{ in}$$

Neutral axis lies 3 in. above the base.




$$I_1 = \frac{1}{12} b_1 h_1^3 + A_1 d_1^2 = \frac{1}{12} (3)(6)^3 + (18)(2)^2 = 126 \text{ in}^4$$

$$I_2 = \frac{1}{12} b_2 h_2^3 + A_2 d_2^2 = \frac{1}{12} (3)(2)^3 + (18)(2)^2 = 78 \text{ in}^4$$

$$I = I_1 + I_2 = 126 + 78 = 204 \text{ in}^4$$

$$y_{top} = 5 \text{ in} \quad y_{bot} = -3 \text{ in}$$




$$M - Pa = 0$$

$$M = Pa = (15)(40) = 600 \text{ kip}\cdot\text{in.}$$

$$\sigma_{top} = -\frac{M y_{top}}{I} = -\frac{(600)(5)}{204} = -14.71 \text{ ksi}$$


$$\sigma_{bot} = -\frac{M y_{bot}}{I} = -\frac{(600)(-3)}{204} = 8.82 \text{ ksi}$$

PROBLEM 4.21



4.21 Knowing that for the extruded beam shown the allowable stress is 12 ksi in tension and 16 ksi in compression, determine the largest couple M that can be applied.

SOLUTION



	A	\bar{y}_o	$A\bar{y}_o$
①	2.25	1.25	2.8125
②	2.25	0.25	0.5625
	4.50		3.375

$$\bar{Y} = \frac{3.375}{4.50} = 0.75 \text{ in}$$

The neutral axis lies 0.75 in. above bottom.

$$y_{\text{top}} = 2.0 - 0.75 = 1.25 \text{ in}, \quad y_{\text{bot}} = -0.75 \text{ in}$$

$$I_1 = \frac{1}{12} b_1 h_1^3 + A_1 d_1^2 = \frac{1}{12} (1.0)(1.0)^3 + (2.25)(0.5)^2 = 0.984375 \text{ in}^4$$

$$I_2 = \frac{1}{12} b_2 h_2^3 + A_2 d_2^2 = \frac{1}{12} (1.0)(1.0)^3 + (2.25)(0.5)^2 = 0.984375 \text{ in}^4$$

$$I = I_1 + I_2 = 1.59375 \text{ in}^4$$


$$|\sigma| = \left| \frac{My}{I} \right| \quad M = \left| \frac{\sigma I}{y} \right|$$

Top: compression $M = \frac{(16)(1.59375)}{1.25} = 20.4 \text{ kip} \cdot \text{in}$

Bottom: tension $M = \frac{(12)(1.59375)}{0.75} = 25.5 \text{ kip} \cdot \text{in}$

Choose the smaller as M_{all} $M_{\text{all}} = 20.4 \text{ kip} \cdot \text{in}$

PROBLEM 4.116



4.116 Determine the stress at points *A* and *B*, (a) for the loading shown, (b) if the 60-kN loads are applied at points 2 and 3 are removed.

SOLUTION

(a) Loading is centric

$$P = 180 \text{ kN} = 180 \times 10^3 \text{ N}$$

$$A = (90)(240) = 21.6 \times 10^3 \text{ mm}^2 = 21.6 \times 10^{-3} \text{ m}^2$$

$$\text{At A and B } \sigma = -\frac{P}{A} = -\frac{180 \times 10^3}{21.6 \times 10^{-3}} = -8.33 \times 10^6 \text{ Pa} = -8.33 \text{ MPa} \quad \blacktriangleleft$$

(b) Eccentric loading

$$P = 180 \text{ kN} = 180 \times 10^3 \text{ N}$$

$$M = (60 \times 10^3)(150 \times 10^{-3}) = 9.0 \times 10^3 \text{ N}\cdot\text{m}$$



$$I = \frac{1}{12}bh^3 = \frac{1}{12}(90)(240)^3 = 103.68 \times 10^6 \text{ mm}^4 = 103.68 \times 10^{-6} \text{ m}^4$$

$$c = 120 \text{ mm} = 0.120 \text{ m}$$

$$\text{At A } \sigma_A = -\frac{P}{A} - \frac{Mc}{I} = -\frac{180 \times 10^3}{21.6 \times 10^{-3}} - \frac{(9.0 \times 10^3)(0.120)}{103.68 \times 10^{-6}} = -13.19 \times 10^6 \text{ Pa} = -13.19 \text{ MPa} \quad \blacktriangleleft$$

$$\text{At B } \sigma_B = -\frac{P}{A} + \frac{Mc}{I} = -\frac{180 \times 10^3}{21.6 \times 10^{-3}} + \frac{(9.0 \times 10^3)(0.120)}{103.68 \times 10^{-6}} = 7.64 \times 10^6 \text{ Pa} = 7.64 \text{ MPa} \quad \blacktriangleleft$$

PROBLEM 4.134



4.134 A vertical force P of magnitude 20 kips is applied at a point C located on the line of symmetry of the cross section of a short column. Knowing that $y = 5$ in., determine (a) the stress at point A , (b) the stress at point B , (c) the location of the neutral axis.

SOLUTION

Locate centroid

Part	A, in^2	\bar{y}, in	$A\bar{y}, \text{in}^3$
①	12	5	60
②	8	2	16
Σ	20		76

$$\bar{y} = \frac{\Sigma A\bar{y}}{\Sigma A} = \frac{76}{20} = 3.8 \text{ in}$$

Eccentricity of load $e = 5 - 3.8 = 1.2 \text{ in.}$

$$I_1 = \frac{1}{12}(6)(2)^3 + (12)(1.2)^2 = 21.28 \text{ in}^4$$

$$I_2 = \frac{1}{12}(2)(4)^3 + (8)(1.8)^2 = 36.587 \text{ in}^4$$

$$I = I_1 + I_2 = 57.867 \text{ in}^4$$

(a) Stress at A $c_A = 3.8 \text{ in}$

$$\sigma_A = -\frac{P}{A} + \frac{Pec_A}{I} = -\frac{20}{20} + \frac{(20)(1.2)(3.8)}{57.867} = 0.576 \text{ ksi}$$

(b) Stress at B $c_B = 6 - 3.8 = 2.2 \text{ in}$

$$\sigma_B = -\frac{P}{A} - \frac{Pec_B}{I} = -\frac{20}{20} - \frac{(20)(1.2)(2.2)}{57.867} = -1.912 \text{ ksi}$$

(c) Location of neutral axis: $\sigma = 0$


$$\sigma = -\frac{P}{A} + \frac{Pea}{I} = 0 \quad \therefore \frac{ea}{I} = \frac{1}{A}$$

$$a = \frac{I}{Ae} = \frac{57.867}{(20)(1.2)} = 2.411 \text{ in}$$

Neutral axis lies 2.411 in. below centroid or $3.8 - 2.411 = 1.389 \text{ in}$ above point A .

Answer 1.389 in from point A

PROBLEM 4.140



4.140 An eccentric axial force P is applied as shown to a steel bar of 25×90 -mm cross section. The strains at A and B have been measured and found to be $\epsilon_A = +350 \mu$ $\epsilon_B = -70 \mu$. Knowing that $E = 200$ GPa, determine (a) the distance d , (b) the magnitude of the force P .

SOLUTION

$$h = 15 + 90 = 105 \text{ mm}$$

$$b = 25 \text{ mm} \quad c = \frac{1}{2}h = 52.5 \text{ mm} = 0.0525 \text{ m}$$

$$A = bh = (25)(105) = 2.625 \times 10^3 \text{ mm}^2 = 2.625 \times 10^{-3} \text{ m}^2$$

$$I = \frac{1}{12}bh^3 = \frac{1}{12}(25)(105)^3 = 2.51875 \times 10^6 \text{ mm}^4 = 2.51875 \times 10^{-6} \text{ m}^4$$

$$y_A = 52.5 - 37.5 = 15 \text{ mm} = 0.015 \text{ m}, \quad y_B = 15 - 52.5 = -37.5 \text{ mm} = -0.0375 \text{ m}$$

Stresses from strain gauges at A and B

$$\sigma_A = E\epsilon_A = (200 \times 10^9)(350 \times 10^{-6}) = 70 \times 10^6 \text{ Pa}$$

$$\sigma_B = E\epsilon_B = (200 \times 10^9)(-70 \times 10^{-6}) = -14 \times 10^6 \text{ Pa}$$

$$\sigma_A = \frac{P}{A} - \frac{My_A}{I} \quad (1)$$

$$\sigma_B = \frac{P}{A} - \frac{My_B}{I} \quad (2)$$

Subtracting $\sigma_A - \sigma_B = -\frac{M(y_A - y_B)}{I}$

$$M = -\frac{I(\sigma_A - \sigma_B)}{y_A - y_B} = -\frac{(2.51875 \times 10^{-6})(84 \times 10^6)}{0.0525} = -2835 \text{ N}\cdot\text{m}$$

Multiplying (2) by y_A and (1) by y_B and subtracting

$$y_A \sigma_B - y_B \sigma_A = (y_A - y_B) \frac{P}{A}$$

$$P = \frac{A(y_A \sigma_B - y_B \sigma_A)}{y_A - y_B} = \frac{(2.625 \times 10^{-3})[(0.015)(-14 \times 10^6) - (-0.0375)(70 \times 10^6)]}{0.0525} = 94.5 \times 10^3 \text{ N}$$


(a) $M = -Pd \therefore d = -\frac{M}{P} = -\frac{-2835}{94.5 \times 10^3} = 0.030 \text{ m} = 30 \text{ mm} \quad \blacktriangleleft$

(b)

$$P = 94.5 \text{ kN} \quad \blacktriangleleft$$


PROBLEM 4.148

4.148 through 4.150 The couple M is applied to a beam of the cross section shown in a plane forming an angle β with the vertical. Determine the stress at (a) point A, (b) point B, (c) point D.



SOLUTION

Locate centroid



	A, in^2	\bar{z}, in	$A\bar{z}, \text{in}^3$
①	16	-1	-16
②	8	2	16
Σ	24		0

The centroid lies at point C

$$I_z = \frac{1}{12}(2)(8)^3 + \frac{1}{12}(4)(2)^3 = 88 \text{ in}^4$$

$$I_y = \frac{1}{12}(8)(2)^3 + \frac{1}{12}(2)(4)^3 = 64 \text{ in}^4$$

$$y_A = -y_B = 1 \text{ in}, \quad y_D = -4 \text{ in}$$

$$z_A = z_B = -4 \text{ in}, \quad z_D = 0$$

$$M_z = 10 \cos 20^\circ = 9.3969 \text{ kip}\cdot\text{in}$$

$$M_y = 10 \sin 20^\circ = 3.4202 \text{ kip}\cdot\text{in}$$



$$(a) \quad \sigma_A = -\frac{M_z y_A}{I_z} + \frac{M_y z_A}{I_y} = -\frac{(9.3969)(1)}{88} + \frac{(3.4202)(-4)}{64} = -0.321 \text{ ksi} \quad \blacktriangleleft$$

$$(b) \quad \sigma_B = -\frac{M_z y_B}{I_z} + \frac{M_y z_B}{I_y} = -\frac{(9.3969)(-1)}{88} + \frac{(3.4202)(-4)}{64} = -0.107 \text{ ksi} \quad \blacktriangleleft$$

$$(c) \quad \sigma_D = -\frac{M_z y_D}{I_z} + \frac{M_y z_D}{I_y} = -\frac{(9.3969)(-4)}{88} + \frac{(3.4202)(0)}{64} = 0.427 \text{ ksi} \quad \blacktriangleleft$$

PROBLEM 4.164

4.164 An axial load P of magnitude 50 kN is applied as shown to a short section of a W 150 × 24 rolled-steel member. Determine the largest distance a for which the maximum compressive stress does not exceed 90 MPa.



SOLUTION

Add y - and z - axes.

For W 150 × 24 rolled-steel section

$$A = 3060 \text{ mm}^2 = 3060 \times 10^{-6} \text{ m}^2$$

$$I_z = 13.4 \times 10^6 \text{ mm}^4 = 13.4 \times 10^{-6} \text{ m}^4$$

$$I_y = 1.83 \times 10^6 \text{ mm}^4 = 1.83 \times 10^{-6} \text{ m}^4$$

$$d = 160 \text{ mm}, \quad b_f = 102 \text{ mm}$$

$$y_A = -\frac{d}{2} = -80 \text{ mm}, \quad z_A = \frac{b_f}{2} = 51 \text{ mm}.$$

$$P = 50 \times 10^3 \text{ N}$$

$$M_z = -(50 \times 10^3)(75 \times 10^{-3}) = -3.75 \times 10^3 \text{ N}\cdot\text{m}$$

$$M_y = -Pa$$

$$\sigma_A = -\frac{P}{A} - \frac{M_z y_A}{I_z} + \frac{M_y z_A}{I_y}$$

$$\sigma_A = -90 \times 10^6 \text{ Pa}$$

$$M_y = \frac{I_y}{z_A} \left\{ \frac{M_z y_A}{I_z} + \frac{P}{A} + \sigma_A \right\}$$



$$= \frac{1.83 \times 10^{-6}}{51 \times 10^{-3}} \left\{ \frac{(-3.75 \times 10^3)(-80 \times 10^{-3})}{13.4 \times 10^{-6}} + \frac{50 \times 10^3}{3060 \times 10^{-6}} + (-90 \times 10^6) \right\}$$

$$= \frac{1.83 \times 10^{-6}}{51 \times 10^{-3}} \left\{ +22.388 + 16.340 - 90 \right\} \times 10^6$$

$$= -1.8398 \times 10^3 \text{ N}\cdot\text{m}$$

$$a = -\frac{M_y}{P} = -\frac{-1.8398 \times 10^3}{50 \times 10^3} = 36.8 \times 10^{-3} \text{ m} = 36.8 \text{ mm}$$

PROBLEM 4.162



4.162 The tube shown has a uniform wall thickness of 0.5 in. For the given loading, determine (a) the stress at points A and B, (b) the point where the neutral axis intersects line ABD.

SOLUTION

Add y- and z- axes as shown.

$$I_z = \frac{1}{12}(3)(5)^3 - \frac{1}{12}(2)(4)^3 = 20.583 \text{ in}^4$$

$$I_y = \frac{1}{12}(5)(3)^3 - \frac{1}{12}(4)(2)^3 = 8.5833 \text{ in}^4$$

$$A = (3)(5) - (2)(4) = 7.0 \text{ in}^2$$

Resultant force and bending couples

$$P = 3 + 6 + 6 = 15 \text{ kips}$$

$$M_z = -(2.5)(3) + (2.5)(6) + (2.5)(6) = 22.5 \text{ kip-in.}$$

$$M_y = -(1.5)(3) - (1.5)(6) + (1.5)(6) = -4.5 \text{ kip-in.}$$

$$(a) \quad \sigma_A = \frac{P}{A} - \frac{M_z y_A}{I_z} + \frac{M_y z_A}{I_y} = \frac{15}{7} - \frac{(22.5)(-2.5)}{20.583} + \frac{(-4.5)(1.5)}{8.5833} = 4.09 \text{ ksi} \quad \blacktriangleleft$$

$$\sigma_B = \frac{P}{A} - \frac{M_z y_B}{I_z} + \frac{M_y z_B}{I_y} = \frac{15}{7} - \frac{(22.5)(2.5)}{20.583} + \frac{(-4.5)(1.5)}{8.5833} = -1.376 \text{ ksi} \quad \blacktriangleleft$$

(b) Let point H be the point where the neutral axis intersects AB.

$$z_H = 1.5, \quad y_H = ?, \quad \sigma_H = 0$$


$$0 = \frac{P}{A} - \frac{M_z y_H}{I_z} + \frac{M_y z_H}{I_y}$$

$$y_H = \frac{I_z}{M_z} \left(\frac{P}{A} + \frac{M_y z_H}{I_y} \right) = \frac{20.583}{22.5} \left\{ \frac{15}{7} + \frac{(-4.5)(1.5)}{8.5833} \right\} = 1.241 \text{ in.}$$

$$2.5 + 1.241 = 3.741 \text{ in.}$$

Answer: 3.741 in. above point A. ◀

PROBLEM 4.150



4.148 through 4.150 The couple M is applied to a beam of the cross section shown in a plane forming an angle β with the vertical. Determine the stress at (a) point A, (b) point B, (c) point D.

SOLUTION

$$I_z = \frac{\pi}{8} r^4 - \left(\frac{\pi}{2} r^2 \right) \left(\frac{4r}{3\pi} \right)^2 = \left(\frac{\pi}{8} - \frac{8}{9\pi} \right) r^4$$

$$= (0.109757)(0.8)^4 = 44.956 \times 10^{-3} \text{ in}^4$$

$$I_y = \frac{\pi}{8} r^4 = \frac{\pi}{8} (0.8)^4 = 160.85 \times 10^{-3} \text{ in}^4$$

$$y_A = y_D = -\frac{4r}{3\pi} = -\frac{(4)(0.8)}{3\pi} = -0.33953 \text{ in.}$$

$$y_B = 0.8 - 0.33953 = 0.46047 \text{ in.}$$

$$z_A = -z_D = 0.8 \text{ in.}, \quad z_B = 0$$

$$M_y = 900 \sin 30^\circ = 450 \text{ lb}\cdot\text{in.}$$

$$M_z = 900 \cos 30^\circ = 779.42 \text{ lb}\cdot\text{in.}$$

$$(a) \quad \sigma_A = -\frac{M_z y_A}{I_z} + \frac{M_y z_A}{I_y} = -\frac{(779.42)(-0.33953)}{44.956 \times 10^{-3}} + \frac{(450)(0.8)}{160.85 \times 10^{-3}} = 8.12 \times 10^3 \text{ psi} = 8.12 \text{ ksi} \quad \blacktriangleleft$$

$$(b) \quad \sigma_B = -\frac{M_z y_B}{I_z} + \frac{M_y z_B}{I_y} = -\frac{(779.42)(0.46047)}{44.956 \times 10^{-3}} + \frac{(450)(0)}{160.85 \times 10^{-3}} = -7.98 \times 10^3 \text{ psi} = -7.98 \text{ ksi} \quad \blacktriangleleft$$

$$(c) \quad \sigma_D = -\frac{M_z y_D}{I_z} + \frac{M_y z_D}{I_y} = -\frac{(779.42)(-0.33953)}{44.956 \times 10^{-3}} + \frac{(450)(-0.8)}{160.85 \times 10^{-3}} = 3.65 \times 10^3 \text{ psi} = 3.65 \text{ ksi} \quad \blacktriangleleft$$