

DESIGN PROBLEMS

Specification of Composition

4.D1 This problem calls for us to compute the concentration of lithium (in wt%) that, when added to aluminum, will yield a density of 2.47 g/cm^3 . Solution of this problem requires the use of Equation 4.10a, which takes the form

$$\rho_{\text{ave}} = \frac{100}{\frac{C_{\text{Li}}}{\rho_{\text{Li}}} + \frac{100 - C_{\text{Li}}}{\rho_{\text{Al}}}}$$

inasmuch as $C_{\text{Li}} + C_{\text{Al}} = 100$. According to the table inside the front cover, the respective densities of Li and Al are 0.534 and 2.71 g/cm^3 . Upon solving for C_{Li} from the above equation, we get

$$\begin{aligned} C_{\text{Li}} &= \frac{100 \rho_{\text{Li}} (\rho_{\text{Al}} - \rho_{\text{ave}})}{\rho_{\text{ave}} (\rho_{\text{Al}} - \rho_{\text{Li}})} \\ &= \frac{(100)(0.534 \text{ g/cm}^3)(2.71 \text{ g/cm}^3 - 2.47 \text{ g/cm}^3)}{(2.47 \text{ g/cm}^3)(2.71 \text{ g/cm}^3 - 0.534 \text{ g/cm}^3)} \\ &= 2.38 \text{ wt\%} \end{aligned}$$